

Solior FL150T

| | |
|---|------------------------|
| Collector Area | 1.85 m ² |
| External Dimensions (Length x Width x Height) | 1970 x 1441 x 1220 mm |
| Mass, Empty | 60 kg |
| Mass, Full | 210 kg |
| Water Content of the Storage Tank | 150 litres |
| Maximum Water Pressure | 8 bar |
| Maximum Temperature, Filled with Water | 95°C |
| Maximum Temperature, Empty | 200°C |
| Connection, Cold Water | ¾" socket |
| Connection, Hot Water | ½" socket |
| Storage Tank | Stainless steel |
| Dome | PMMA |
| Base | HDPE |
| Frame & Support | Galvanised steel |
| Solar Absorption | 94% |
| Infrared Emission | 5% |
| Average Annual Heat Loss Factor (Collector Area) | 2,5 W/m ² K |
| Optical Efficiency | 75% |
| Weight on the Roof | 200 kg |
| Maximum Wind Speed (V_m) | 33 m/s |
| Maximum Electric Power | 0 W |
| Average Annual Electricity Consumption | None |
| Lowest Acceptable Ambient Temperature | 0°C |

- The Solior FL150 T is recyclable
- Compliant with norms and standards EN 12975, EN 12976.
- CE-compliant; 5-year warranty on components (condition apply)